



ATTORNEY DOCKET No. 04-01-07A

APPLICATION  
FOR UNITED STATES LETTERS PATENT

TITLE  
PORTABLE VIBRATORY CONCRETE SCREED

INVENTOR  
Kenny D. Breeding  
10922 Garrison Road  
Little Rock, AR 72223

CROSS-REFERENCE TO RELATED APPLICATIONS  
This application claims benefit of provisional application number  
60/438701

FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT  
Not Applicable

SPECIFICATION

TO ALL WHOM IT MAY CONCERN

Be it known that I, Kenny D. Breeding, a citizen of the United States, have  
invented new and useful improvements in a portable vibratory concrete screed as  
described in this specification.

1 BACKGROUND OF THE INVENTION

2  
3 Field of the Invention

4  
5 As is known, the usage of concrete as a building material is widespread  
6 and ever growing, where, although various mechanical finishing approaches are  
7 already available, striking and/or grading primarily remains a hand-operation.  
8

9 A typical procedure employed in connection with the placing of concrete  
10 involves strike-off; bull float, as for rock wash down; and, finally, hand-finishing,  
11 typically involving the use of trowels. The preceding is time consuming and,  
12 therefore, a need has arisen for more rapidly completing the latter but, at the  
13 same time, with professional quality results.  
14

15 The present invention relates to devices for surfacing concrete and, more  
16 particularly, to vibrating screeds for concrete surfacing of the type having an  
17 elongated blade mounted transversally at the bottom of a pair of hand held  
18 handles with a motor being adapted to transmit to the blade a vibratory  
19 movement.  
20

21 2. Description of the Prior Art

22  
23 Conventional vibrating screeds comprise, for instance, an elongated blade  
24 extending horizontally and transversally at lower ends of a pair of handles  
25 adapted to be hand held and operated for displacing the screed over a concrete  
26 surface. A motor is provided above the blade and between the handles and has  
27 its shaft extending vertically downwards from the motor to the blade and is  
28 connected thereat such that, with a counterweight or a cam-like arrangement, it  
29 imparts oscillatory movement to the blade of high frequency but low amplitude.  
30

1           The pair of handles permit an easy and constant correction of the level of  
2 the concrete with minimum effort. The blade may have different lengths, for  
3 example between 4 and 12 feet. A throttle control of the motor is provided at one  
4 of the handles such that the speed of the motor may be monitored and adjusted  
5 as the blade is displaced over the concrete being surfaced.

6  
7           Numerous screeds employ vibratory action to tamp and smooth concrete  
8 in the final finishing step. U.S. Pat. No. 4,340,351 describes a vibratory concrete  
9 screed used in the final finishing of concrete. This screed requires two operators.  
10 U.S. Pat. No. 4,641,995 describes a vibratory concrete screed, which rides on  
11 forms to screed narrow strips of concrete, such as walks. This screed is mounted  
12 on the operator via a complicated harness counter-weighted frame and is  
13 powered by electricity. As a result, the screed requires electrical power on site  
14 and the screed requires manipulation of lengthy extension cords.

15  
16           Escalating labor costs and the unavailability of qualified concrete helpers  
17 have pushed the concrete finishers' profitability margin down continually, thus  
18 forcing rising costs of construction nationwide. The current standard method of  
19 wet screeding freshly poured concrete is with a 2" by 4" board 8' to 20' long with  
20 one or two men hand working the concrete all day long as two to four laborers,  
21 "puddlers", push the fresh concrete, "mud", in place with concrete rakes.

22  
23           The hand process is not only slow, inefficient and labor intensive, it is also  
24 often requires the addition of more water to the concrete mix to make it more  
25 workable. The additional water reduces the strength of the concrete, causing  
26 voids and weak spots. The addition of water to produce slumps of 6" to 8", so the  
27 finisher can effectively hand "Wet Screed" the fresh concrete, is common in the  
28 industry nationwide today. The hand process limits the finisher to the average  
29 pour of 6,000 to a maximum of 8,000 square feet of slab per day for a crew of  
30 six.

1 It is known in the art to provide rotatable handles and telescoping arms,  
2 for example U.S. Pat. No. 6,296,467. These devices provide only a limited range  
3 of adjustment and are clumsy to operate. The adjustment settings frequently  
4 change due to the constant vibrations inherent in portable vibrating screeds.  
5 These changes cause operator discomfort and require the operator to stop work  
6 to make the necessary corrections before continuing on the work site. Other prior  
7 art devices have folding handle bars that simply fold in or down and up. They  
8 remain mainly rigid and require considerable space for transportation or storage.  
9

10 In all current production models of portable vibrating screeds, the vibrator  
11 in an integral part of the housing that is built in or is permanently attached to the  
12 blade adapter. The unit must be completely disassembled during the routine  
13 maintenance required for all vibrational tools of this type. This only increases the  
14 down time of the screed and the operator thereby, increasing costs.

15 Extruded L-shaped screed blades are known in the art. Many of the  
16 blades are thin, tapered and elongated blades that are flexible over the lengths  
17 common is these free floating screeds. Many do not transmit the vibrational  
18 energy in a uniform manner over the entire length of the blade.

19 All prior art portable vibrating screeds have the power unit permanently  
20 mounted to a specific screed blade adapter, which is used to attach to a specific  
21 screed blade style or shape. Multiple screeds are necessary for an operator to  
22 obtain the benefit of a particular screed blade style or shape in specific  
23 applications. For instance, a particular job site may present conditions where a  
24 triangular shaped blade would be more efficient than an L-shaped blade.

25 It is, therefore, an object of the present invention to provide a portable  
26 vibratory concrete screed. The concrete screed includes a screed blade including  
27 a flat bottom surface extending between a front edge of the screed blade and a  
28 rear edge of the screed blade. The screed also includes a vibrator cartridge  
29 assembly, with an eccentric weight, releasably coupled to the screed blade.

1 Further, the screed includes an adjustable handle bar assembly extending from  
2 the power housing assembly and coupling a motor to the power platform  
3 assembly which drives the vibrator cartridge assembly thereby rotating the  
4 eccentric weight and vibrating the screed blade.  
5

6 It is another object of the present invention to provide a portable vibratory  
7 concrete screed wherein the vibrator cartridge assembly includes a drive shaft  
8 upon which the eccentric weight is mounted.  
9

10 It is a further object of the present invention to provide a portable vibratory  
11 concrete screed including a screed blade mounting assembly coupling the  
12 vibrator cartridge assembly to the screed blade.  
13

14 It is also an object of the present invention to provide a portable vibratory  
15 concrete screed wherein the screed blade mounting assembly includes a  
16 mounting bracket supporting the vibrator cartridge assembly above the screed  
17 blade.  
18

19 It is another object of the present invention to provide a portable vibratory  
20 concrete screed wherein the handle bar assembly is coupled to the power  
21 platform assembly, and vibration isolators are positioned between the handle bar  
22 assembly and the blade adapter assembly to lessen vibrations transmitted to a  
23 user.  
24

25 It is another object of the present invention to provide a portable vibratory  
26 concrete screed wherein the handle bar assembly is compounded in folding  
27 capability and capable of bilateral axis movements yielding virtually any position  
28 for operator height and comfort coupled to the power platform assembly, and  
29 vibration isolators are positioned between the handle bar assembly and the blade  
30 adapter assembly to lessen vibrations transmitted to a user.

1           It is a further object of the present invention to provide a portable vibratory  
2 concrete screed wherein the handle bar assembly is coupled to the power  
3 platform assembly, and the power platform assembly has an integral handle for  
4 lifting and carrying the screed

5  
6           It is also an object of the present invention to provide a portable vibratory  
7 concrete screed wherein the vibratory assembly includes an end cap secured to  
8 the vibration cartridge assembly to encase the eccentric weight.

9  
10          It is another object of the present invention to provide a portable vibratory  
11 concrete screed wherein the vibrator cartridge assembly includes at least one  
12 bearing on the drive shaft to lessen vibrations.

13  
14          It is another object of the present invention to provide a portable vibratory  
15 concrete screed wherein the vibrator cartridge assembly easily removable for  
16 quick replacement and repair to reduce downtime to the screed operator.

17  
18          It is another object of the present invention to provide a portable vibratory  
19 concrete screed wherein the vibrator cartridge assembly easily removable for  
20 quick replacement and repair.

21  
22          It is another object of the present invention to provide a portable vibratory  
23 concrete screed wherein the vibrator cartridge assembly simply requires  
24 removing the bolts and bearing cartridge, replace the cartridge with a new or  
25 rebuilt cartridge, attach the unbalanced weights and continue on the job site.

26  
27          It is a further object of the present invention to provide a portable vibratory  
28 concrete screed wherein the motor is secured to the power platform assembly at  
29 distal end of the handle bar assembly.

1           It is also an object of the present invention to provide a portable vibratory  
2 concrete screed wherein the handle bar assembly includes an adjustable handle  
3 grip tube.  
4

5           It is also an object of the present invention to provide a portable vibratory  
6 concrete screed wherein an exact pin locking system for holding the handle grip  
7 tubes in an angular position that stays locked in place while being subjected to  
8 the inherent vibrational forces generated during concrete screeding.  
9

10          It is also an object of the present invention to provide a portable vibratory  
11 concrete screed wherein the adjustable handle grip tube is secured in position by  
12 a plurality of set pins.  
13

14          It is another object of the present invention to provide a portable vibratory  
15 concrete screed wherein the handle grip tube is adjustable to suit users of  
16 different heights.

17          It is another object of the present invention to provide a portable vibratory  
18 concrete screed wherein the handle bar assembly is adjustable along the mid  
19 point for adjustment to suit users of different heights.  
20

21          It is another object of the present invention to provide a portable vibratory  
22 concrete screed wherein the handle bar assembly contains a kick stand along  
23 the mid point for supporting the screed.

24          It is also an object of the present invention to provide a portable vibratory  
25 concrete screed wherein the handle bar assembly folds over the motor for  
26 transportation and storage.  
27  
28

1           It is a further object of the present invention to provide a portable vibratory  
2 concrete screed wherein the screed blade has an L-shaped cross section  
3 containing structural gussets for strength and vibration transmission.  
4

5           It is also an object of the present invention to provide a portable vibratory  
6 concrete screed wherein the screed blade adapter assembly is capable of  
7 receiving many different blade shapes.

8           It is also an object of the present invention to provide a portable vibratory  
9 concrete screed wherein the screed blade adapter assembly is capable of  
10 receiving many different blade styles.  
11

12           The present invention allows the wet screeding of concrete quickly and  
13 efficiently with only one operator and two puddlers, while doubling the potential  
14 daily pour to 13,000 to 16,000 square feet per day; literally as fast as the  
15 concrete trucks can pour it. The increased efficiency also doubles the income  
16 potential of the concrete finisher. Simultaneously, the present screed, with its  
17 floating vibratory action, produces a much higher quality slab having greater  
18 strength, no voids and no weak spots. The present screed also allows one  
19 additional hour for final finishing by working the rock down and bringing the fat to  
20 the surface.  
21

22           In addition to doubling the potential surface area that may be efficiently wet  
23 screeded each day, the present screed's light weight portability and single  
24 operator ease of operation reduces the required crew size from the six (6)  
25 workers normally required with conventional hand wet screeding methods to four  
26 (4) workers.  
27

28           Even doubling the area of production, the crew and operator of the present  
29 screed are vastly less physically fatigued at days end due to the ease of  
30 operation of the invention and its efficient high quality work.



1 This is one of the most valuable benefits of the invention since it is directly  
2 beneficial to the health and well being of both operator and crew.

3  
4 Additionally, due to the invention's light weight an operator can when  
5 required, utilize the device as a bull float temporarily, with the power vibratory  
6 action on idle, to smooth out a spot or two inadvertently missed by the operator.

7  
8 Further, due to the interchangeability design of the screed blade, the  
9 present screed may be used as a straight edge to check the flatness of the slab  
10 after the slab has been powered troweled. With the power vibratory action on  
11 idle, the screed can be pulled along the surface of the slab. If a hump or bump is  
12 detected (by vibrations at the screed blade), the operator pushes the present  
13 screed back, applies a little throttle, and the sharp cutting edge of the screed  
14 blade will cut through and peel the bump off the surface of the slab.

15  
16 Other objects and advantages of the present invention will become  
17 apparent from the following detailed description when viewed in conjunction with  
18 the accompanying drawings, which set forth certain embodiments of the  
19 invention.

20  
21 In view of the shortcomings of hand processing wet concrete and prior art  
22 vibratory screeds, a need exists for a portable vibrating screed which effectively  
23 and efficiently prepares wet concrete for use. The need exists for a screed that  
24 has a removal/replaceable vibrator cartridge. A need exists for a screed that has  
25 folding handle bars that are compound in folding design. A need exists for a  
26 screed with extruded blade gussets for strength. A need exists for a screed with  
27 blade interchangeable attachments. The present invention provides such a  
28 screed.

1     DETAIL DESCRIPTION OF THE INVENTION

2  
3             Fig. 24 illustrates a vibrating screed in accordance with the present  
4 invention and generally comprising an elongated surfacing blade 40, a tubular  
5 handle bar assembly 36 extending upwardly and rearwardly from the blade 40,  
6 and a motor 37 for imparting vibratory movement to the blade 40 such that, when  
7 the blade 40 is displaced over a wet concrete surface, it surfaces, i.e. smoothes,  
8 the concrete surface. The motor 37 may be powered by gasoline or other fuels  
9 and may also by electric.

10  
11            More particularly, the tubular handle bar assembly 36 comprises a pair of  
12 handle grip tubes 25 adjustably connected to an upper cross bar 24. The cross  
13 bar 24 extends between and is fixed to a pair of handle bar mid-sections 23 by  
14 an upper handle bar clamp assembly illustrated in Fig. 18. The clamp assembly is  
15 comprised of a handle clamp base 28 and a handle clamp top 29. The handle bar  
16 mid-sections 23 extend downwards and are rotatably attached to a lower  
17 crossbar 60. Base tubes 26 and 27 terminate in attachment plates 65 which are  
18 connected to a power platform assembly, shown in Fig. 8, by headless bolts 70  
19 with nuts at their opposed ends or by standard nut and bolts.

20  
21            The power platform assembly 35, Figs. 23 and 10, comprises a motor  
22 mount assembly, Fig. 8, wherein a motor 37 is connected to the upper end of the  
23 motor mount body 16 as shown in Fig. 23. Motor 37 is coupled the drive  
24 connector 15 by drive shaft 21. Drive connector 15 rotates within the nylon  
25 bearing spacer 19 thereby rotating drive joint 14. Motor mount body 16 is  
26 attached to the power platform plate 20 by standard nuts and bolts. Handle  
27 flange 17 is an integral part of the motor mount assembly contributes to the ease  
28 of lifting and carrying the screed. Flex joint 38 is received by the power platform  
29 assembly to rotate the vibrator cartridge assembly.

1 The vibrator cartridge assembly, shown in Figs. 1, 2 and 3, removably  
2 coupled to the flex joint 38 at one end to the vibrator drive joint 4. Drive joint 4  
3 rotates upon bearings 1 and within bearing housing 2.

4  
5 Vibrator drive shaft 3 is connected at one end to drive joint 4 and to a set  
6 of adjustable eccentric weights 11 and fixed eccentric weights 12 at the other as  
7 shown in Fig. 6. Bearings 1 are contained within the vibrator cartridge by  
8 retaining ring 5. The weights 11 and 12 and vibration cartridge assembly are  
9 contained within the eccentric cover 9 that is held in place by bolts secured the  
10 eccentric cover mount 13. The cover mount is secured to the vibration cartridge  
11 assembly and the blade adapter bracket assembly 8 by standard bolts and nuts.  
12 Sealing ring 39 prevents concrete, dirt and other foreign materials from  
13 accessing the vibration cartridge assembly or the power platform assembly.

14  
15 The blade adapter bracket assembly 34 ,shown in Figs 5, 6 ,7 and 23,  
16 attaches to the power platform assembly 35 separated by vibrational isolators 7.  
17 The adapter bracket 8 attaches directly to a screed blade 40 as shown in Figs 25  
18 and 26 through bolt holes 49. Blade 40 is generally L shaped on cross sectional  
19 view, illustrated in Fig. 26, having a top surface 43 ,a finishing surface 45 a  
20 cutting edge-46 and a trailing edge 41. Structural gussets 42 extent the length of  
21 the blade providing more uniform transmission of vibrational energy. Adapters 51  
22 may be employed as shown in Figs 27 – 32 to connect bracket 8 to different  
23 shaped screed blades 50.

24  
25 Accordingly, when in operation, an operator may adjust the height and  
26 angle of the handle grip tube 25 to any position for the operators comfort. Grip  
27 tube 25 adjustment is accomplished by loosening the bolts securing handle  
28 clamp base and top 28, 29 thereby allowing the upper cross bar 24 to be rotated  
29 in a plane vertical to the ground thus adjusting the grip tube to any operators  
30 height. The bolts are then tightened, forcing the clamp base and top to engage  
31 the upper cross bar 24 through friction, ribs or grooves in the upper cross bar.

1 By loosening the retaining bolt extending through the fixed handle knuckle 32  
2 and the adjustable handle knuckle 33, as shown in Fig 19, lateral adjustment of  
3 grip tube 25 is accomplished. As shown in Fig. 20, locking pins 30 located on the  
4 fixed handle knuckle 32 are inserted into corresponding adjustment holes located  
5 on the adjustable handle knuckle 33 thereby preventing the grip tube from  
6 losing its adjustment even after lengthy periods of vibration.

7  
8 The operator has complete control over the height of the handle bar mid  
9 section 23 through adjustment of the lower clamping area as illustrated in Figs.  
10 16 and 17. Adjustment is accomplished by loosening the bolts securing handle  
11 clamp base and top 28, 29 thereby allowing the lower cross bar 60 to rotate in a  
12 plane perpendicular to base tube 26 and 27 thus adjusting the handle bar mid  
13 section to any operators height. The bolts are then tightened, forcing the clamp  
14 base and top to engage the lower cross bar 60 through friction, ribs or grooves in  
15 the lower cross bar.

16  
17 The motor 37 causes motor drive shaft 21 to rotate. Shaft 21 being  
18 releasably coupled to motor 37 a clamp. Drive shaft 21 causes drive joint 14 and  
19 drive connector 15 to rotate as shaft 21 is fixed to connector 15. This rotation is  
20 transferred from the power platform assembly to the vibration cartridge through  
21 flex joint 38. The flex joint in turn rotatably drives the vibrator drive shaft 3  
22 causing a rotation of the adjustable eccentric weight 11 and the fixed eccentric  
23 12 which, due to its eccentricity, imparts vibration to the blade adapter assembly  
24 34 and thus to the blade 40. The vibration isolators 7 reduce the amount of  
25 vibrations transmitted to the handle bar assembly 36 and the operator.

26  
27 The speed and intensity of the vibrations are controlled by the throttle  
28 hand grip attached to the handle grip tube 25. The action of the throttle control is  
29 transmitted to the motor 37 through a cable attached to the handle bar assembly  
30 by clips.

1 The vibrational force is transmitted through the blade adapter 8 and along the  
2 blade 40 where structural gussets 42 strengthen blade 40 and apply the  
3 vibrational force evenly across the wet concrete.  
4

5 In the event the bearing cartridge 6 should fail, the operator removes the  
6 blade adapter assembly 34 to access the bolts attaching the bearing cartridge 6  
7 to the blade adapter 8. The bearing cartridge 6 is replaced and the blade adapter  
8 assembly reattached to the power platform assembly.  
9

10 A kick stand 31 is pivotally attached along the mid point of the handle bar  
11 assembly 36 and rotates to directly support the distal end of the screed on the  
12 ground. The kick stand is held in place by a clip located on the upper end of the  
13 handle bar assembly.  
14

15 The screed can be folded into a compact form for transportation to and  
16 from a work site or for storage. The bolts securing handle clamp base and top 28,  
17 29 thereby allowing the upper cross bar 24 to be rotated in a plane vertical to the  
18 ground. The upper cross bar is then rotated such that the grip tubes 25 are  
19 parallel to handle bar mid section 23 as shown in Fig. 34. The bolts are then  
20 tightened, forcing the clamp base and top to engage the upper cross bar 24  
21 through friction, ribs or grooves in the upper cross bar. The retaining bolt  
22 extending through the fixed handle knuckle 32 and the adjustable handle knuckle  
23 33 is loosened, as shown in Fig 19, allowing the lateral adjustment of grip tube  
24 25. Grip tubes 25 are rotated inward and placed in their shipping/storage position  
25 Fig. 34. As shown in Fig. 20, locking pins 30 located on the fixed handle knuckle  
26 32 are inserted into corresponding adjustment holes located on the adjustable  
27 handle knuckle 33 thereby locking the grip tube into position. The bolts securing  
28 the clamp base and top of the lower clamping area, as illustrated in Figs. 16 and  
29 17, are loosened.  
30

1 Final adjustment of the handle bar assembly 36 for storage/shipping is  
2 accomplished by lifting the handle bar mid-section thus rotating the lower cross  
3 bar 60. The upper cross bar 24 is brought over motor 37 and placed near the  
4 handle bar assembly 36. The bolts securing the clamp base and top of the lower  
5 clamping area are then tightened, forcing the clamp base and top to engage the  
6 lower cross bar 60 through friction, ribs or grooves in the lower cross bar.

7  
8 Referring to Figs. 27 and 28, an alternative embodiment is shown where  
9 the blade adapter assembly 34 is attached to a Multi-Quip style screed blade  
10 50MQ by adapter components 51MQ .

11  
12 Referring to Figs. 29 and 30, an alternative embodiment is shown where  
13 the blade adapter assembly 34 is attached to a Vibra-Strike style screed blade  
14 50L by adapter components 51L .

15  
16 Referring to Figs. 31 and 32, an alternative embodiment is shown where  
17 the blade adapter assembly 34 is attached to a Weber style screed blade 50W by  
18 adapter components 51W.